



## HANDLE-IT® SA Series

Model 600

### Model 800

Model 800XHT

Model 850PS

Model 850PS XHT

Model 1100AC

Model 1200UL



3 year  
Warranty

Part Number: SWM-SA-0800

### Full Set of Functions & Options

#### Electronic Film Tension

100 max average pallets per day!

### Technical Specifications

Wrap Height	86"
Turntable Diameter	59"
Max Pallet Size	48" x 80" (93" Diagonal)
Turntable Height	3"
Weight Capacity	4,400 lbs
Electronic Film Tension	Variable
Power Supply	110V, 10 Amp
Total Machine Footprint	93" long x 60" wide
Machine Weight	600 lbs
Turntable Speed	13 RPM

## Handle-It® Model 800

The Handle-It® Model 800 offers top-of-the-line functions and features at a great price. It is ideal for those who are looking for an efficient machine capable of handling moderate to high volumes of pallets per day.

Standard features on the 800 include 86" max wrap height, user-friendly control panel, variable electronic film tension, and many other elements cleverly designed to make this unit a must-have in any facility looking to improve and streamline their packaging operations.

# HANDLE-IT®

## Semi-Automatic Stretch Wrapper

### Product Specifications

- Electronic printed circuit board for the management of the cycle
- Frequency controller for turntable speed adjustment (from 3 to 13 RpM)
- Frequency controller for carriage speed adjustment (speed going up and speed going down can be set differently)
- Turntable size 59"
- Maximum wrapping height: 86"
- Maximum size of the pallet: 48" x 80" (93" Diagonal)
- Maximum loading weight: 4400lbs
- Electromagnetic brake for film stretching
- Photocell for pallet height detection
- Safety stop at the base of the carriage
- Stop at 0 position
- Power board IP54
- 4 digit display
- 2 access keys (including lock mode)
- Many parameters available at upper password level
- Reinforcing operation
- 3 working cycles: ascent/descent; topsheet; only ascent
- 9 wrap programs can be saved by the customer
- 9 additional recordable playback cycles can be saved
- 3 year warranty




**Adjustable parameters by the control panel:** cycle selection, bottom turns, top turns, rotation speed, carriage speed going up, carriage speed going down, film tension.

### Available Options

- Integrated Scale
- Loading Ramp
- Top Press
- Photocell for Dark Loads
- Upgrade to the SWM-SA-850PS for 250% power film pre-stretch.



**Electromagnetic film tension** with easy film threading



**Rack & Pinion carriage drive system** for added reliability

